

IKO CRBC 9016 thrust roller bearings

Offer High Quality Brand IKO CRBC 9016 thrust roller bearings .Contact Us 130 Outer Diameter (mm) Online to Get 280x130x58 Size (mm) Best Quote.

| | |
|-------------------------------|------------|
| Size (mm) | 280x130x58 |
| Bore Diameter (mm) | 280 |
| Outer Diameter (mm) | 130 |
| Width (mm) | 58 |
| d | 130 mm |
| D | 280 mm |
| B | 58 mm |
| D1 | 234.2 mm |
| F | 167 mm |
| r1,2 – min. | 4 mm |
| r3,4 – min. | 4 mm |
| s | 3.7 mm |
| da – min. | 147 mm |
| da – max. | 163 mm |
| db – min. | 170 mm |
| Da – max. | 261.4 mm |
| ra – max. | 3 mm |
| rb – max. | 3 mm |
| Basic dynamic load rating – C | 720 kN |
| Basic static load rating – C0 | 750 kN |
| Fatigue load limit – Pu | 81.5 kN |
| Reference speed | 2400 r/min |

| | |
|---------------------------|--|
| Limiting speed | 3000 r/min |
| Calculation factor – kr | 0.15 |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 16.445 |
| EAN | 7316577043566 |
| Product Group | B04144 |
| Bore Profile | Straight |
| Cage Material | Steel |
| Precision Class | RBEC 1 ISO P0 |
| Number of Rows of Rollers | Single Row |
| Separable | Inner Ring – Both Sides |
| Rolling Element | Cylindrical Roller Bearing |
| Profile | Complete with Outer and Inner Ring |
| Snap Ring | No |
| Internal Clearance | C0-Medium |
| Retainer | Yes |
| Relubricatable | Yes |
| Inch – Metric | Metric |
| Other Features | High Capacity Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID |
| Long Description | 130MM Bore; Straight Bore Profile; 280MM Outside Diameter; 58MM Width; Steel Cage Material; RBEC 1 |
| UNSPSC | 31171547 |
| Harmonized Tariff Code | 8482.50.00.00 |

| Noun | Bearing |
|------------------------------|------------------------------|
| Manufacturer Item Number | NU 326 ECJ |
| Weight / LBS | 36.222 |
| Outside Diameter | 11.024 Inch 280 Millimeter |
| Width | 2.283 Inch 58 Millimeter |
| Bore | 5.118 Inch 130 Millimeter |
| bore diameter: | 130 mm |
| static load capacity: | 750 kN |
| outside diameter: | 280 mm |
| precision rating: | Not Rated |
| overall width: | 58 mm |
| maximum rpm: | 3000 RPM |
| flanges: | (2) Outer Ring |
| bearing material: | Steel |
| bore type: | Straight |
| cage material: | Steel |
| number of rows: | 1 |
| finish/coating: | Uncoated |
| internal clearance: | C0 |
| closure type: | Open |
| ring separation: | Separable Ring |
| outer ring width: | 58 mm |
| operating temperature range: | Maximum of +300 °F |
| fillet radius: | 3 mm |
| dynamic load capacity: | 720 kN |
| series: | NU3 |
| D1 ≈ | 234.2 mm |
| r1,2 min. | 4 mm |
| r3,4 min. | 4 mm |

| | |
|-----------------------------|-----------|
| s max. | 3.7 mm |
| da min. | 147 mm |
| da max. | 163 mm |
| db min. | 170 mm |
| Da max. | 261.4 mm |
| ra max. | 3 mm |
| rb max. | 3 mm |
| Basic dynamic load rating C | 720 kN |
| Basic static load rating C0 | 750 kN |
| Fatigue load limit Pu | 81.5 kN |
| Calculation factor kr | 0.15 |
| Limiting value e | 0.2 |
| Axial load factor Y | 0.6 |
| Mass bearing | 16.1 kg |
| Angle ring | HJ 326 EC |