

IKO CRBC 9016 thrust roller bearings

Offer High Quality Brand IKO CRBC 9016 thrust roller bearings .Contact Us 130 Outer Diameter (mm) Online to Get 280x130x58 Size (mm) Best Quote.

Size (mm)	280x130x58
Bore Diameter (mm)	280
Outer Diameter (mm)	130
Width (mm)	58
d	130 mm
D	280 mm
B	58 mm
D1	234.2 mm
F	167 mm
r1,2 – min.	4 mm
r3,4 – min.	4 mm
s	3.7 mm
da – min.	147 mm
da – max.	163 mm
db – min.	170 mm
Da – max.	261.4 mm
ra – max.	3 mm
rb – max.	3 mm
Basic dynamic load rating – C	720 kN
Basic static load rating – C0	750 kN
Fatigue load limit – Pu	81.5 kN
Reference speed	2400 r/min

Limiting speed	3000 r/min
Calculation factor – kr	0.15
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	16.445
EAN	7316577043566
Product Group	B04144
Bore Profile	Straight
Cage Material	Steel
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring – Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C0-Medium
Retainer	Yes
Relubricatable	Yes
Inch – Metric	Metric
Other Features	High Capacity Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Long Description	130MM Bore; Straight Bore Profile; 280MM Outside Diameter; 58MM Width; Steel Cage Material; RBEC 1
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00

Noun	Bearing
Manufacturer Item Number	NU 326 ECJ
Weight / LBS	36.222
Outside Diameter	11.024 Inch 280 Millimeter
Width	2.283 Inch 58 Millimeter
Bore	5.118 Inch 130 Millimeter
bore diameter:	130 mm
static load capacity:	750 kN
outside diameter:	280 mm
precision rating:	Not Rated
overall width:	58 mm
maximum rpm:	3000 RPM
flanges:	(2) Outer Ring
bearing material:	Steel
bore type:	Straight
cage material:	Steel
number of rows:	1
finish/coating:	Uncoated
internal clearance:	C0
closure type:	Open
ring separation:	Separable Ring
outer ring width:	58 mm
operating temperature range:	Maximum of +300 °F
fillet radius:	3 mm
dynamic load capacity:	720 kN
series:	NU3
D1 ≈	234.2 mm
r1,2 min.	4 mm
r3,4 min.	4 mm

s max.	3.7 mm
da min.	147 mm
da max.	163 mm
db min.	170 mm
Da max.	261.4 mm
ra max.	3 mm
rb max.	3 mm
Basic dynamic load rating C	720 kN
Basic static load rating C0	750 kN
Fatigue load limit Pu	81.5 kN
Calculation factor kr	0.15
Limiting value e	0.2
Axial load factor Y	0.6
Mass bearing	16.1 kg
Angle ring	HJ 326 EC