

# IKO GBR 142216 U needle roller bearings

Browse 60 mm d IKO GBR 142216 U needle roller bearings Categories in the Manufacturers 46 mm T Online Free. including .

|                             |            |
|-----------------------------|------------|
| d                           | 60 mm      |
| D                           | 95 mm      |
| T                           | 46 mm      |
| 2B                          | 46 mm      |
| b                           | 7 mm       |
| K                           | 4.5 mm     |
| r3,4 min.                   | 1.5 mm     |
| r5 min.                     | 0.6 mm     |
| da max.                     | 67 mm      |
| Da min.                     | 85 mm      |
| Da max.                     | 87 mm      |
| Ca min.                     | 4 mm       |
| ra max.                     | 1.5 mm     |
| rc max.                     | 0.6 mm     |
| Basic dynamic load rating C | 173 kN     |
| Basic static load rating C0 | 245 kN     |
| Fatigue load limit Pu       | 27 kN      |
| Reference speed             | 4300 r/min |
| Limiting speed              | 6700 r/min |
| Calculation factor e        | 0.43       |
| Calculation factor Y1       | 1.6        |
| Calculation factor Y2       | 2.3        |

|                       |         |
|-----------------------|---------|
| Calculation factor Y0 | 1.6     |
| Mass bearing pair     | 1.22 kg |