

IKO GBR 283720 needle roller bearings

Enjoy High Margins on Competitive Pricing.Great 180.975 mm da
Wholesale Products 359.999 mm Da at Low Costs.

da	180.975 mm
Da	359.999 mm
Ca	107.798 mm
A1	203.2 mm
A2	358.775 mm
S	4.763 mm
ba	83.344 mm
H	419.1 mm
H1	209.55 mm
H2	85.725 mm
L	749.3 mm
R1	122.237 mm
R2	42.862 mm
RG	1 NPT
PG	1/4 NPT
h	62.706 mm
Housing	SSAFS 540
Bearing	22240 CCK/W33
Adapter sleeve assembly	SNW 40×7.1/8
Stabilizing ring	SR-40-34
Taconite seal	TER 158
End plug (suffix Y)	EPR 21
Max. speed for Taconite seal	425 r/min

P60°	557 kN
P90°	334 kN
P120°	207 kN
P150°	185 kN
P180°	222 kN
Pa	58.7 kN
Mass pillow block	267 kg
Cap bolt	1 1/4-7 UNC
Cap bolt recommended tightening torque	2467.6 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 1/2-13 UNC
Initial grease fill	2154.6 g