

IKO GBRI 203320 UU needle roller bearings

Can't find what you're looking for IKO GBRI 203320 UU needle roller bearings ? Our 26 mm B expert Representatives be 80 mm d in contact with you shortly!

d	80 mm
D	140 mm
B	26 mm
rs min	2 mm
Radial clearance class	C3
Mass	1.4 kg
Dynamic load, C	72.5 kN
Static load, C ₀	53 kN
Fatigue limit load, C _u	2.3 kN
f ₀	14.6
N _{lim} (oil)	5,300 rpm
N _{lim} (grease)	4,500 rpm
Min operating temperature, T _{min}	-60 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	5.6 Hz
Characteristic outer ring frequency, BPF ₀	4.13 Hz
Characteristic inner ring frequency, BRF ₀	5.87 Hz
da min	89 mm
Da max	131 mm

ra max	2 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	1.72
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Brass
Internal Clearance	C3-Loose
Inch – Metric	Metric
Long Description	80MM Bore; 140MM Outside Diameter; 26MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Fi
Other Features	Deep Groove Riveted Solid Cage
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	3.13056
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	5.512 Inch 140 Millimeter
Outer Race Width	1.024 Inch 26 Millimeter

Bore	3.15 Inch 80 Millimeter
------	---------------------------