

IKO GE 180GS-2RS plain bearings

IKO GE 180GS-2RS plain bearings Product Brochures , Manufacturing 370x260x150 Size (mm) Service . Get Your Free.

Size (mm)	370x260x150
Bore Diameter (mm)	370
Outer Diameter (mm)	260
Width (mm)	150
d	260 mm
D	370 mm
B	150 mm
C	110 mm
α	7 °
dk	325 mm
r1 – min.	1.1 mm
r2 – min.	1.1 mm
da – min.	273 mm
da – max.	288 mm
Da – min.	321.5 mm
Da – max.	359 mm
ra – max.	1 mm
rb – max.	1 mm
Basic dynamic load rating – C	8650 kN
Basic static load rating – C0	14300 kN
Specific factor dinamic load – K	300 N/mm ²
Specific factor static load – K0	500 N/mm ²

Lubricant	Maintenance free – dry lubrication
Design (sliding contact surface combination)	Steel/PTFE fabric
Sealing solution	Triple-lip seals
α	7 °
r1 min.	1.1 mm
r2 min.	1.1 mm
da min.	273 mm
da max.	288 mm
Da min.	321.5 mm
Da max.	359 mm
ra max.	1 mm
rb max.	1 mm
Basic dynamic load rating C	8650 kN
Basic static load rating C0	14300 kN
Specific dynamic load factor K	300 N/mm ²
Specific static load factor K0	500 N/mm ²
Mass plain bearing	51.5 kg