IKO KT 222912 needle roller bearings

Manufacturers of all are Mounted Bearing Engineering Group represented in our partial list of clients. Contact Gary for a complete IKO KT 222912 needle roller bearings list of clients and projects.

| Engineering Group | Mounted Bearing |
|-------------------------|-------------------------|
| Shaft Size | 2-15/16 in |
| Shaft Size Type | Imperial |
| Full Timken Part Number | QAAFL15A215SB |
| Locking Style | Double Concentric |
| Weight | 23 lb |
| Housing Style | Four-Bolt Square Flange |
| UPC Code | 0883450021005 |
| Dimension BC | 7.88 in |
| Dimension C | 4.50 in |
| Dimension D | 6.630 in |
| Dimension E | 5.56 in |
| Dimension F | 7.19 in |
| Dimension H | 1.06 in |
| Dimension J (Bolt Size) | 0.75 in |
| Dimension L Exp | 3.85 in |
| Dimension L Fix | 3.77 in |
| Dimension M | 2.37 in |
| Dimension N | 2.930 in |
| Dimension RAA | 0.97 in |
| Dimension SAA | 4.74 in |

| CO — Static Load | 54100 lb |
|-------------------------------------|-----------|
| C — Dynamic Load (Basic) | 49900 lb |
| e — Geometry Factor | 0.22 |
| Y1 - Geometry Factor | 3.01 |
| Y2 - Geometry Factor | 4.48 |
| Oil Lubrication — M/N Seal | 1600 rpm |
| Oil Lubrication — T Seal | 2900 rpm |
| Oil Lubrication — B/C/O Seal | 1300 rpm |
| Grease Lubrication — M/N Seal | 1600 rpm |
| Grease Lubrication — T Seal | 2400 rpm |
| Grease Lubrication — B/C/O Seal | 1300 rpm |
| Float | 0.083 in |
| Shaft Tolerance | 0.0020 in |
| Eng Internal Radial Clearance — Min | 0.0020 |
| Eng Internal Radial Clearance — Max | 0.0031 |
| Pre Install Clearance Min | 0.0020 in |
| Pre Install Clearance Max | 0.0031 in |