

IKO KT 253216 needle roller bearings

How do I place an EMERGENCY 25x52x15 Size (mm) order for a IKO KT 253216 needle roller bearings 52 Outer Diameter (mm) that I want to pick up 25 Bore Diameter (mm) at a our store?

Size (mm)	25x52x15
Bore Diameter (mm)	25
Outer Diameter (mm)	52
Width (mm)	15
d	25 mm
Fw	31,5 mm
D	52 mm
B	15 mm
C	15 mm
r min.	1 mm
r1 min.	0,6 mm
Weight	0,14 Kg
Basic dynamic load rating (C)	29,3 kN
Basic static load rating (C0)	27,7 kN
(Grease) Lubrication Speed	12000 r/min
Inventory	0.0
Manufacturer Name	NACHI
Minimum Buy Quantity	N/A
Weight / Kilogram	0.141
EAN	4991893393163
Product Group	B04144
Bore Profile	Straight

Cage Material	Nylon
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring – Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C0-Medium
Retainer	Yes
Relubricatable	Yes
Inch – Metric	Metric
Other Features	High Capacity Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Long Description	25MM Bore; Straight Bore Profile; 52MM Outside Diameter; 15MM Width; Nylon Cage Material; RBEC 1
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer Item Number	NU205 EG
Weight / LBS	0.31
Width	0.591 Inch 15 Millimeter
Outside Diameter	2.047 Inch 52 Millimeter
Bore	0.984 Inch 25 Millimeter
Enclosure	Open
Bore Type	Cylindrical Bore
Configuration	Single Row

Bore Size	25 mm
Fillet Radius/Chamfer	1 mm
r1	0.6 mm
Dynamic Load Rating	29,300 N
Static Load Rating	27,700 N
Limiting Speed – Grease	12,000 rpm
Limiting Speed – Oil	14,000 rpm
Radial Clearance	0.020 to 0.045 mm
db (min)	30 mm
db (max)	31 mm
dc (min)	34 mm
dd (min)	37 mm
Da (max)	46 mm
ra (max)	1 mm
ra1 (max)	0.6 mm