

# IKO KT 354216 needle roller bearings

We work closely with our IKO KT 354216 needle roller bearings manufacturing partners to bring N/A Minimum Buy Quantity the 0.0 Inventory best value to customers.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| EAN                       | 0013992048813  |
| Weight / US pound         | 16.9   |
| Product Group             | B04144   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Clamp Collar   |
| Housing Style             | 2 Bolt Pillow Block                                      |
| Rolling Element           | Cylindrical Roller Bearing                               |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Expansion  |
| Mounting Bolts            | 16 Millimeter  |
| Relubricatable            | Yes  |
| Insert Part Number        | LSM45BX  |
| Seals                     | Triple Lip Labyrinth                                     |
| Housing Configuration     | 2 Piece Split  |
| Inch – Metric             | Metric   |
| Other Features            | Single Row   Light Duty   With Support   Wide Inner Ring |
| UNSPSC                    | 31171511   |
| Harmonized Tariff Code    | 8483.20.40.80  |

|                               |  |
|-------------------------------|--|
| Noun                          | Bearing                                  |
| Keyword String                | Pillow Block                             |
| Weight / LBS                  | 16.9                                     |
| Nominal Bolt Center to Center | 8.4 Inch   214 Millimeter                |
| Actual Bolt Center to Center  | 8.4 Inch   214Millimeter                 |
| B                             | 2.756 Inch   70 Millimeter               |
| d                             | 1.772 Inch   45 Millimeter               |
| Bolt Spacing Minimum          | 0 Inch   0Millimeter                     |
| D                             | 2.362 Inch   60 Millimeter               |
| Bolt Spacing Maximum          | 0 Inch   0Millimeter                     |
| Shaft Size                    | 45 mm                                    |
| Seal Type                     | Aluminium Triple Labyrinth               |
| Bearing Type                  | Split Cylindrical Expansion Type         |
| Support Type                  | Two-Bolt Plummer Block                   |
| Series Type                   | Light Series                             |
| Pillow/Plummer Block Style    | Split Cylindrical Housed Unit – Standard |
| Bolt Size                     | 2 x M16                                  |
| Weight                        | 23 lb                                    |
| Dimension H                   | 2.756 in                                 |
| Dimension H1                  | 1.0 in                                   |
| Dimension H2                  | 6.2 in                                   |
| Dimension J                   | 8.4 in                                   |
| Dimension L                   | 10.6 in                                  |
| Dimension M                   | 2.4 in                                   |
| Housing Width                 | 3.9 in                                   |
| Cr – Dynamic Load Rating      | 18659 lbf                                |
| Cor – Static Load Rating      | 19558 lbf                                |

|               |   |
|---------------|---|
| Maximum Speed | 4630 rpm  |
| Note          | This product line was formerly known as "Revolvo" |