IKO KT 354220 needle roller bearings

With over 10170 full-service stores, our 0.0 Inventory IKO KT 354220 needle roller bearings inventory is extensive and our NTN Manufacturer Name parts are priced right. within 24 hours. This helps you maximize your N/A Minimum Buy Quantity productivity by saving time and your hard-earned dollars.

| Inventory | 0.0 |
|----------------------|------------------------------|
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight | 0.172 |
| EAN | 4547359431414 |
| Product Group | B04270 |
| Enclosure | 0pen |
| Precision Class | ABEC 7 ISO P4 |
| Material — Ball | Steel |
| Number of Bearings | 2 (1 Pair) |
| Contact Angle | 30 Degree |
| Preload | Light |
| Raceway Style | 1 Rib Outer Ring |
| Cage Material | Nylon |
| Rolling Element | Ball Bearing |
| Mounting Arrangement | Duplex-Back to Back |
| Flush Ground | Yes |
| Inch — Metric | Metric |
| Other Features | Single Row Angular Contact |

| Long Description | 55MM Bore; 90MM Outside Diameter; 36MM Width; Open Enclosure; ABEC 7 ISO P4 Precision; Steel Ball |
|----------------------------------|--|
| UNSPSC | 31171531 |
| Harmonized Tariff Code | 8482.10.50.28 |
| Noun | Bearing |
| Keyword String | Angular Contact Ball |
| Manufacturer Item Number | 7011DB/GNP4 |
| Weight / LBS | 0.38 |
| D | 3.543 Inch 90 Millimeter |
| В | 1.417 Inch 36 Millimeter |
| d | 2.165 Inch 55 Millimeter |
| bore diameter: | 55 mm |
| cage material: | Brass |
| outside diameter: | 90 mm |
| finish/coating: | Uncoated |
| overall width: | 36 mm |
| inner ring width: | 18 mm |
| contact angle: | 30 ° |
| maximum rpm (oil): | 12960 rpm |
| duplex type: | Back to Back |
| <pre>maximum rpm (grease):</pre> | 9520 rpm |
| closure type: | 0pen |
| outer ring width: | 18 mm |
| operating temperature range: | -40 to 120 ºC |
| fillet radius: | 1.1 mm |
| bearing material: | High Carbon Chrome Steel |
| manufacturer product page: | Click here |
| precision rating: | ISO Class 4 |