## IKO KT 606827 needle roller bearings

Advance IKO KT 606827 needle roller bearings SKF Manufacturer Name is your source for N/A Minimum Buy Quantity quality and accessories. shop online for home delivery or pick up in one of our 10000 . 0.0 Inventory

| Inventory                 | 0.0                       |
|---------------------------|---------------------------|
| Manufacturer Name         | SKF                       |
| Minimum Buy Quantity      | N/A                       |
| Weight                    | 3.86                      |
| EAN                       | 7316577026514             |
| Product Group             | M06288                    |
| Number of Mounting Holes  | 3                         |
| Mounting Method           | Concentric Collar         |
| Housing Style             | 3 Bolt Round Flange Block |
| Rolling Element           | Spherical Roller Bearing  |
| Housing Material          | Cast Iron                 |
| Expansion / Non-expansion | Expansion                 |
| Mounting Bolts            | 1/2 Inch                  |
| Relubricatable            | Yes                       |
| Insert Part Number        | 22208                     |
| Seals                     | Garter Spring             |
| Housing Configuration     | 1 Piece Solid             |
| Pilot Configuration       | No Pilot                  |
| Inch — Metric             | Inch                      |

| Long Description                      | 3 Bolt Round Flange Block;<br>1-7/16" Bore; 5" Bolt<br>Circle; 4.3" Bolt Spacing;<br>1 Piece S |
|---------------------------------------|--|
| Other Features                        | Double Row   Heavy Duty  <br>Open End   With Set Screw   |
| UNSPSC                                | 31171501   |
| Harmonized Tariff Code                | 8483.20.40.80  |
| Noun                                  | Bearing  |
| Keyword String                        | Flanged  |
| Manufacturer Item Number              | FYR 1.7/16-3   |
| Weight / LBS                          | 8.5  |
| D                                     | 2.75 Inch   69.85<br>Millimeter  |
| Bolt Spacing                          | 4.3 Inch   110 Millimeter  |
| d                                     | 1.438 Inch   36.525<br>Millimeter  |
| Cartridge Pilot Diameter              | 0 Inch   0 Millimeter  |
| Nominal Bolt Circle Diameter<br>Round | 5 Inch   127 Millimeter  |
| Cartridge Pilot Depth                 | 0 Inch   0 Millimeter  |
| bore diameter:                        | 1-7/16 in  |
| expansion type:                       | Non-Expansion Bearing (Fixed)  |
| bolt center-to-center length:         | 5.0000 in  |
| seal type:                            | Radial Shaft Seal  |
| overall length/diameter:              | 6.2500 in  |
| overall depth:                        | 2-7/8 in   |
| flange mounting type:                 | Four-Bolt Round  |
| radial dynamic load capacity:         | 16600 lb   |
| bearing type:                         | Spherical Roller   |

| radial static load capacity: | 18300 lb            |
|------------------------------|---------------------|
| housing construction:        | Solid Flange Mount  |
| operating temperature range: | -5 to +230 °F       |
| bore type:                   | Round               |
| maximum rpm:                 | 1700 RPM            |
| duty type:                   | Standard Duty       |
| finish/coating:              | Uncoated            |
| housing material:            | Cast Iron           |
| lubrication type:            | Lubrication Fitting |
| locking device:              | Set Screw           |
| series:                      | 222                 |