

# IKO NA 6912U needle roller bearings

Various types 38.1 mm da and sizes to accommodate 85.001 mm Da your IKO NA 6912U needle roller bearings requirements.

da	38.1 mm
Da	85.001 mm
Ca	28.804 mm
A1	60.325 mm
A2	88.9 mm
S	4.763 mm
ba	22.225 mm
H	112.713 mm
H1	57.15 mm
H2	20.637 mm
J min.	158.75 mm
J max.	177.8 mm
L	209.55 mm
N1	15.875 mm
R1	28.575 mm
R2	12.7 mm
RG	1/8 NPT
PG	1/8 NPT
h	25.4 mm
Housing	SAF 509
Bearing	1209 EKTN9
Adapter sleeve assembly	SNW 9×1.1/2
Stabilizing ring	SR-9-0

Labyrinth ring	2 x LER 18
End plug (suffix Y)	EPR 3
Bearing limiting speed	11000 r/min
P60°	20.9 kN
P90°	12.5 kN
P120°	7.56 kN
P150°	6.67 kN
P180°	8.01 kN
Pa	2.54 kN
Mass pillow block	5.17 kg
Cap bolt	2 x 7/16-14 UNC
Cap bolt recommended tightening torque	61 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.5 in
Initial grease fill	51.03 g