

# IKO NAU 4908UU cylindrical roller bearings

Enjoy High 80 Bore Diameter (mm) Margins on Competitive 80x100x10 Size (mm) Pricing.Great Wholesale Products at Low Costs.

Size (mm)	80x100x10
Bore Diameter (mm)	80
Outer Diameter (mm)	100
Width (mm)	10
d	80 mm
D	100 mm
B	10 mm
C	10 mm
r min.	0,6 mm
da min.	84 mm
da max	84,5 mm
Da max.	96 mm
ra max.	0,6 mm
Weight	0,151 Kg
Basic dynamic load rating (C)	12,7 kN
Basic static load rating (C0)	14,5 kN
(Grease) Lubrication Speed	6 000 r/min
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	0.07
EAN	0029176030314

Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Non-Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	80MM Bore; 100MM Outside Diameter; 10MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1   ISO P0;
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6816VV
Weight / LBS	0.144
Outer Race Width	0.394 Inch   10 Millimeter
Bore	3.15 Inch   80 Millimeter
Outside Diameter	3.937 Inch   100 Millimeter
bore diameter:	80 mm
closure type:	Double Sealed
outside diameter:	100 mm
internal clearance:	Normal Clearance
overall width:	10 mm
manufacturer upc number:	029176030314

bore type:	Round
SRI	2.88
hidYobi	6816VV
LangID	1
D_	100
SREX	0.015
B_	10
da min	84
hidTable	ecat_NSRDGB
SRE	2.88
mass	0.151
GRS rpm	6000
ra	0.6
SRIX	0.015
D_a	96
SRIN	-0.015
C0	14.5
fo	17.4
SREN	-0.015
DE_	95.556
Prod_Type3	DGGB_SR_VV
DA_	5.556
bomp	0
Z_	27
yobi	6816VV
C_conv	12700
ALPHA_	0
SDM_	90
r	0.6

KBRG	6151
SBRG	18
DI_	84.444