

IKO NAU 4911 cylindrical roller bearings

offers a IKO NAU 4911 cylindrical roller bearings selection of Genuine at Wholesale Prices. We 52×61.913×17 Size (mm) are 61,913 Outer Diameter (mm) a IKO NAU 4911 cylindrical roller bearings Certified Parts Retailer

Size (mm)	52×61.913×17
Bore Diameter (mm)	52
Outer Diameter (mm)	61,913
Width (mm)	17
d	61.913 mm
A1	52 mm
A2	17 mm
J	143 mm
L	175 mm
T	73.7 mm
H	19 mm
B	65.1 mm
s1	39.7 mm
Basic dynamic load rating – C	52.7 kN
Basic static load rating – C0	36 kN
Limiting speed	100 r/min
Limiting temperature – T	350 °C
Mass bearing unit	4.65 kg
Grub (set) screw – G2 – 3/8-24 UNF	3/824 UNF
Hexagonal key size for grub screw – H	4.762 mm

Recommended tightening torque for grub screw	16.5 N·m
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	4.27
EAN	7316571381299
Product Group	M06110
Number of Mounting Holes	4
Mounting Method	Set Screw
Housing Style	4 Bolt Square Flange Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	5/8 Inch
Relubricatable	Yes
Insert Part Number	YAR 212-207-2FW/VA228
Seals	M Seal
Housing Configuration	1 Piece Solid
Pilot Configuration	No Pilot
Inch – Metric	Inch
Long Description	4 Bolt Square Flange Block; 2-7/16" Bore; 7.9" Bolt Circle; 5-5/8" Bolt Spacing; 1 Pi
Other Features	Single Row Standard Duty Wide Inner Race Open End High Temperature Bearing with Graphite H
UNSPSC	31171501

Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Flanged
Manufacturer Item Number	FY 2.7/16 TF/VA228
Weight / LBS	9.4
Cartridge Pilot Diameter	0 Inch 0 Millimeter
Bolt Spacing	5.625 Inch 142.88 Millimeter
Bore	2.438 Inch 61.925 Millimeter
Cartridge Pilot Depth	0 Inch 0 Millimeter
Length Thru Bore	2.563 Inch 65.09 Millimeter
Nominal Bolt Circle Diameter Round	7.9 Inch 200 Millimeter
bore diameter:	2.4375 in
radial static load capacity:	8100 lbf
bolt center-to-center length:	143 mm
seal type:	Contact Seal
overall length/diameter:	175 mm
length through bore:	73.7 mm
bore type:	Round
operating temperature range:	-30 to +120 °F
mounting type:	Four-Bolt Flange
finish/coating:	Uncoated
housing material:	Cast Iron
lubrication type:	Cannot Be Relubricated
locking device:	Set Screw
series:	FY

expansion type:	Non-Expansion Bearing (Fixed)
manufacturer upc number:	7316571381299
N	19 mm
Basic dynamic load rating C	52.7 kN
Basic static load rating C0	36 kN
Limiting temperature T max.	350 °C
Grub (set) screw G2	3/8-24 UNF
Hexagonal key size for grub screw N	4.763 mm
Attachment bolts, recommended metric size G	16 mm
Bearing	YAR 212-207-2FW/VA228