

IKO NAXI 3030 complex bearings

Manufacturers 85 Bore Diameter (mm) of all are represented in our partial list of clients. Contact Gary for a complete IKO NAXI 3030 complex bearings list of 85x120x18 Size (mm) clients and projects.

Size (mm)	85x120x18
Bore Diameter (mm)	85
Outer Diameter (mm)	120
Width (mm)	18
d	85 mm
D	120 mm
B	18 mm
C	18 mm
r min.	1,1 mm
da min.	91,5 mm
da max	94 mm
Da max.	113,5 mm
ra max.	1 mm
Weight	0,536 Kg
Basic dynamic load rating (C)	32 kN
Basic static load rating (C0)	29,6 kN
Reference speed	3 000 r/min
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.526

EAN	4547359587975
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	85MM Bore; 120MM Outside Diameter; 18MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0;
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6917LLU/2AS
Weight / LBS	1.162
Outside Diameter	4.724 Inch 120 Millimeter
Bore	3.346 Inch 85 Millimeter
Outer Race Width	0.709 Inch 18 Millimeter
bore diameter:	85 mm
precision rating:	ISO Class 0
outside diameter:	120 mm
finish/coating:	Uncoated
overall width:	18 mm

bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Sealed
inner ring width:	18 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	18 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	3000 rpm
internal clearance:	CN
fillet radius:	1.1 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	6300 RPM
dynamic load capacity:	32000 N
series:	69
static load capacity:	29600 N
manufacturer product page:	Click here