

# IKO NAXI 6040 complex bearings

Browse IKO NAXI 6040 complex bearings Categories in 17 mm d the Manufacturers Online Free. including .

d	17 mm
D	40 mm
B	12 mm
a min	1.9 mm
a max	2.06 mm
Ca min	2.92 mm
Ca max	3.18 mm
rs min	0.6 mm
rNs min	0.5 mm
D3 max	38.1 mm
b min	1.35 mm
b max	1.65 mm
r0 max	0.4 mm
D4 max	44.6 mm
f	1.12 mm
Snap ring reference	R40
Radial clearance class	C3
Mass	0.07 kg
Dynamic load, C	9.6 kN
Static load, C0	4.6 kN
Fatigue limit load, Cu	0.21 kN
f0	12.8
Nlim (oil)	21,000 rpm

Nlim (grease)	18,000 rpm
Min operating temperature, Tmin	-60 °C
Characteristic cage frequency, FTF	0.38 Hz
Characteristic rolling element frequency, BSF	3.78 Hz
Characteristic outer ring frequency, BPF0	2.63 Hz
Characteristic inner ring frequency, BRFI	4.37 Hz
da min	21 mm
Da max	36 mm
ra max	0.6 mm
rNa max	0.5 mm
Db min	45.5 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.066
EAN	4547359560589
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	Yes
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C3-Loose
Inch – Metric	Metric

Long Description	17MM Bore; 40MM Outside Diameter; 12MM Outer Race Diameter; Open; Ball Bearing; ABEC 1   ISO P0; No
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6203UNRC3
Weight / LBS	0.143
Bore	0.669 Inch   17 Millimeter
Outside Diameter	1.575 Inch   40 Millimeter
Outer Race Width	0.472 Inch   12 Millimeter
bore diameter:	17 mm
finish/coating:	Uncoated
outside diameter:	40 mm
bearing material:	High Carbon Chrome Steel
overall width:	12 mm
cage material:	Steel
bore type:	Round
inner ring width:	12 mm
closure type:	Open
outer ring width:	12 mm
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	18000 rpm
snap ring included:	With Snap Ring

maximum rpm (oil):	21000 rpm
internal clearance:	C3
fillet radius:	0.6 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	21000 RPM
dynamic load capacity:	9600 N
series:	62
static load capacity:	4600 N
manufacturer product page:	<a href="#">Click here</a>
precision rating:	ISO Class 0