

IKO SNM 24-60 plain bearings

IKO SNM 24-60 plain bearings manufacturer and global supplier of reliable ball and roller 0.0 Inventory ... IKO SNM 24-60 plain bearings Industries Products Manufacturing & Engineering and Agricultural Bearings designed to meet the unique requirements of our N/A Minimum Buy Quantity targeted industries.

| | |
|--------------------------|---------------|
| Inventory | 0.0 |
| Manufacturer Name | TIMKEN |
| Minimum Buy Quantity | N/A |
| EAN | 0883450508001 |
| Weight / US pound | 0.01 |
| Product Group | M06110 |
| Shaft Size | 4.5 in |
| Shaft Size Type | Imperial |
| Weight | 110.000 lb |
| UPC Code | 0883450508001 |
| Type E Open Cover Number | EUDR-4 7/16 |
| Nose Diameter | 8.86 in |
| Nose Bore Diameter | 7 in |
| Dimension B | 6-3/4 in |
| Dimension H | 13-1/2 in |
| Dimension A | 4-5/8 in |
| Dimension N2 | 5.875 in |
| Dimension J | 11-3/4 in |
| Dimension A3 | 1-1/2 in |
| Bolt Diameter | 3/4 in |
| Dimension E | 3 in |

| | |
|--|---|
| Dimension A1 | 1 in |
| Dimension D 1 | 10-1/4 in |
| Dimension d1 | 6-47/64 in |
| Dimension A2 | 1-15/16 in |
| Dimension Ac | 6.363 in |
| Dimension d2 | 8.25 in |
| e | 0.53 |
| X (if $F_a/F_r \leq e$) | 0.87 |
| Y (if $F_a/F_r \leq e$) | 1.63 |
| X (if $F_a/F_r > e$) | 0.7 |
| Y (if $F_a/F_r > e$) | 1.97 |
| K Factor | 1.13 |
| C90 Dynamic Load Rating ² | 33000 lb |
| C0 Static Load Rating | 188400 lb |
| Fa-max Maximum Permissible Thrust Load ³ | 6908 lb |
| Fr-max Maximum Allowable Slip Fit Radial Load ⁴ | 27000 lb |
| Max. Speed ⁵ | 1360 rpm |
| Note | Note: All units have a 1/8 pipe thread grease fitting The Maximum Permissible Thrust Load applies to |