

IKO TA 2116 Z needle roller bearings

Browse IKO TA 2116 Z needle roller bearings Categories 15 Bore Diameter (mm) in the Manufacturers Online 15x32x9 Size (mm) Free. including . 32 Outer Diameter (mm)

Size (mm)	15x32x9
Bore Diameter (mm)	15
Outer Diameter (mm)	32
Width (mm)	9
d	15 mm
D	32 mm
B	9 mm
C	9 mm
rn	0,3 mm
a	2,06 mm
b	1,35 mm
f	1,12 mm
r min.	0,3 mm
r θ max.	0,4 mm
D1	30,15 mm
D2	36,7 mm
da min.	17 mm
da max	19 mm
Da max.	30 mm
ra max.	0,3 mm
Weight	0,031 Kg
Basic dynamic load rating (C)	5,6 kN

Basic static load rating (C0)	2,83 kN
(Grease) Lubrication Speed	24 000 r/min
(Oil) Lubrication Speed	28 000 r/min
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	0.03
EAN	0029176037191
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	Yes
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	15MM Bore; 32MM Outside Diameter; 9MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No F
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6002NR
Weight / LBS	0.07
Outside Diameter	1.26 Inch 32 Millimeter
Outer Race Width	0.354 Inch 9 Millimeter

Bore	0.591 Inch 15 Millimeter
SRI	2.46
hidYobi	6002NR
LangID	1
ro	0.4
D_	32
SREX	0.03
B_	9
da min	17
hidTable	ecat_NSRDGB
Oil rpm	28000
SRE	2.52
Cy	2.9
mass	0.031
GRS rpm	24000
ra	0.3
SRIX	0.015
D_a	30
SRIN	-0.015
C0	2.83
fo	13.9
SREN	0
DE_	28.262
Prod_Type3	DGBB_SR_NR_OT
DA_	4.762
bomp	0
Z_	9
yobi	6002NR
Dx	37.5

C_conv	5600
ALPHA_	0
SDM_	23.5
r	0.3
KBRG	6101
SBRG	10
DI_	18.738