

# IKO TAF 243216/SG needle roller bearings

Welcome to 500 Outer Diameter (mm) the IKO TAF 243216/SG needle roller bearings online 300x500x200 Size (mm) seller.

|                               |             |
|-------------------------------|-------------|
| Size (mm)                     | 300x500x200 |
| Bore Diameter (mm)            | 300         |
| Outer Diameter (mm)           | 500         |
| Width (mm)                    | 200         |
| d                             | 300 mm      |
| D                             | 500 mm      |
| T                             | 200 mm      |
| C                             | 160 mm      |
| r min.                        | 6 mm        |
| r1 min.                       | 2 mm        |
| da min.                       | 328 mm      |
| Da min                        | 466 mm      |
| ra max.                       | 5 mm        |
| rb max.                       | 2 mm        |
| Weight                        | 144 Kg      |
| Basic dynamic load rating (C) | 2270 kN     |
| Basic static load rating (C0) | 4630 kN     |
| (Grease) Lubrication Speed    | 470 r/min   |
| (Oil) Lubrication Speed       | 630 r/min   |
| Calculation factor (e)        | 0,35        |
| Calculation factor (Y0)       | 1,91        |
| Bearing No.                   | 46360A      |
| r(min)                        | 6           |

|                    |      |
|--------------------|------|
| r1(min)            | 2    |
| Cr                 | 2860 |
| C0r                | 4630 |
| Cu                 | 231  |
| Grease lub.        | 470  |
| Oil lub.           | 630  |
| da(min)            | 328  |
| Da(min)            | 490  |
| Sa(min)            | 20   |
| ra(max)            | 5    |
| rb(max)            | 2    |
| e                  | 0.35 |
| Y2                 | 1.95 |
| Y3                 | 2.90 |
| Y0                 | 1.91 |
| (Refer.) Mass (kg) | 144  |