

IKO TAF 293820/SG needle roller bearings

offers a IKO TAF 293820/SG needle roller bearings selection of Genuine 17x2x7 Size (mm) at Wholesale Prices. We are a IKO TAF 293820/SG needle roller bearings Certified Parts Retailer

Size (mm)	17x2x7
Bore Diameter (mm)	17
Outer Diameter (mm)	2
Width (mm)	7
d	17 mm
A1	2 mm
A2	7 mm
B	27.4 mm
B4	4 mm
Da – min.	44 mm
J	63 mm
H	7.1 mm
s1	15.9 mm
T	17.9 mm
Basic dynamic load rating – C	9.6 kN
Basic static load rating – C0	4.8 kN
Fatigue load limit – Pu	0.2 kN
Permissible radial housing load	max. 2.5 kN
Weight	0.22 kg
Thread – G2	M6x0.75
Hexagonal key size for grub screw – H	3 mm
Housing material	Pressed steel

Da min.	44 mm
N	7.1 mm
Basic dynamic load rating C	9.56 kN
Basic static load rating C0	4.75 kN
Fatigue load limit Pu	0.2 kN
Permissible radial housing load max.	2.5 kN
Mass unit	0.22 kg
Thread grub screw G2	M6x0.75
Hexagonal key size for grub screw N	3 mm
Recommended tightening torque for grub screw	4 N·m
Recommended diameter for attachment bolts, mm G	6 mm
Recommended diameter for attachment bolts, inch G	0.25 in
Bearing	YAR 203-2F
Housing	PF 40