

# IKO TAF 91612 needle roller bearings

IKO TAF 91612 needle roller bearings, Units and Housings CAD models , 24x12x17.5 Size (mm) Manufacturing Service . Get 12 Outer Diameter (mm) Your Free.

Size (mm)	24x12x17.5
Bore Diameter (mm)	24
Outer Diameter (mm)	12
Width (mm)	17,5
d	12 mm
D	24 mm
B	17.5 mm
C	16 mm
F	16 mm
r <sub>1,2</sub> – min.	0.3 mm
da – min.	14 mm
Da – max.	22 mm
ra – max.	0.3 mm
Basic dynamic load rating, radial direction – C	8.1 kN
Basic static load rating, radial direction – C <sub>0</sub>	9.6 kN
Basic dynamic load rating, axial direction – C	2.1 kN
Basic static load rating, axial direction – C <sub>0</sub>	1.9 kN
Fatigue load limit, radial direction – P <sub>u</sub>	1.1 kN

Fatigue load limit, axial direction – Pu	0.083 kN
Reference speed	22000 r/min
Limiting speed	26000 r/min
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.037
EAN	7316577739933
Product Group	B04144
bore diameter:	12 mm
closure type:	Open
outside diameter:	24 mm
fillet radius:	0.3 mm
overall width:	17.5 mm
lubrication type:	Grease
bearing type:	Needle Roller/Angular Contact Ball
cage material:	Steel
operating temperature range:	Max 250 °F
series:	NKIB
radial dynamic load capacity:	8.09 kN
manufacturer product page:	<a href="#">Click here</a>
radial static load capacity:	9.65 kN
manufacturer upc number:	7316577739933
bearing material:	Steel
weight:	0.095 lb
maximum rpm:	26000 rpm
r1,2 min.	0.3 mm

da min.	14 mm
Da max.	22 mm
ra max.	0.3 mm
Basic dynamic load rating, radial direction C	8.09 kN
Basic static load rating, radial direction C0	9.65 kN
Basic dynamic load rating, axial direction C	2.07 kN
Basic static load rating, axial direction C0	1.92 kN
Fatigue load limit, radial direction Pu	1.14 kN
Fatigue load limit, axial direction Pu	0.083 kN
Mass bearing	0.043 kg