

IKO TAM 1420 needle roller bearings

Our 0.0 Inventory highly-skilled and factory-trained service experts have the resources to help you with all your IKO TAM 1420 needle roller bearings needs – including routine maintenance, major repairs, warranty service, and equipment inspections.

| | |
|---------------------------|------------------------------------|
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 11.788 |
| EAN | 7316576623554 |
| Product Group | B04144 |
| Bore Profile | Straight |
| Cage Material | Brass |
| Precision Class | RBEC 1 ISO P0 |
| Number of Rows of Rollers | Single Row |
| Separable | Inner Ring – Both Sides |
| Rolling Element | Cylindrical Roller Bearing |
| Profile | Complete with Outer and Inner Ring |
| Snap Ring | No |
| Internal Clearance | C3-Loose |
| Retainer | Yes |
| Relubricatable | Yes |
| Inch – Metric | Metric |

| | |
|--------------------------|--|
| Other Features | High Capacity Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID |
| Long Description | 110MM Bore; Straight Bore Profile; 240MM Outside Diameter; 50MM Width; Brass Cage Material; RBEC 1 |
| UNSPSC | 31171547 |
| Harmonized Tariff Code | 8482.50.00.00 |
| Noun | Bearing |
| Manufacturer Item Number | NU 322 ECM/C3 |
| Weight / LBS | 25.964 |
| D | 9.449 Inch 240 Millimeter |
| d | 4.331 Inch 110 Millimeter |
| B | 1.969 Inch 50 Millimeter |
| bore diameter: | 110 mm |
| precision rating: | RBEC 1 (ISO Class Normal) |
| outside diameter: | 240 mm |
| maximum rpm: | 3400 RPM |
| overall width: | 50 mm |
| bearing material: | Steel |
| flanges: | (2) Outer Ring |
| cage material: | Brass |
| bore type: | Straight |
| finish/coating: | Uncoated |
| number of rows: | 1 |
| closure type: | Open |
| internal clearance: | C3 |
| application: | Piston Type Machines, Rolling Mills, Spindles/Machine Tools |

| | |
|------------------------------|--------------------|
| ring separation: | Separable Ring |
| outer ring width: | 50 mm |
| operating temperature range: | Maximum of +300 °F |
| fillet radius: | 2.5 mm |
| dynamic load capacity: | 530 kN |
| series: | NU3 |
| static load capacity: | 540 kN |