

INA 712178700 tapered roller bearings

INA 712178700 tapered roller bearings with 19.05 Bore Diameter (mm) easy-to-use parts graphics, giving you the ability to check parts availability, pricing, 31 Width (mm) examine remanufactured options.

Bore Diameter (mm)	19.05
Width (mm)	31
d	19.05 mm
Da	55 mm
A1	2 mm
B	31 mm
G	8 mm
H	91 mm
H1	– mm
J	71,5 mm
L	–
N	8,7 mm
T	20,3 mm
A2	8 mm
Weight	0,3 Kg
Basic dynamic load rating (C)	12,7 kN
Basic static load rating (C0)	6,55 kN
Housing material	Pressed steel
B4	4.5 mm
Da min.	51 mm
s1	18.3 mm

Basic dynamic load rating C	12.7 kN
Basic static load rating C ₀	6.55 kN
Fatigue load limit P _u	0.28 kN
Permissible radial housing load max.	3.3 kN
Mass unit	0.33 kg
Thread grub screw G2	1/4-28 UNF
Hexagonal key size for grub screw N	3.175 mm
Recommended tightening torque for grub screw	4 N·m
Recommended diameter for attachment bolts, mm G	8 mm
Recommended diameter for attachment bolts, inch G	0.3125 in
Bearing	YAR 204-012-2F
Housing	PF 47