

# INA 712179800 angular contact ball bearings

What is INA 712179800 angular contact ball bearings in mechanical engineering? Manufacturing Service . Upload your CAD file 66.675 mm da for an 67.793 mm Ca instant.

da	66.675 mm
Da	170 mm
Ca	67.793 mm
A1	98.425 mm
A2	160.338 mm
S	4.763 mm
ba	46.038 mm
H	209.55 mm
H1	107.95 mm
H2	44.45 mm
J min.	269.875 mm
J max.	320.675 mm
J1	53.975 mm
L	361.95 mm
N1	19.05 mm
R1	63.5 mm
R2	26.988 mm
RG	3/8 NPT
PG	1/8 NPT
h	42.862 mm
Housing	FSAF 616
Bearing	22316 EK

Adapter sleeve assembly	SNW 116×2.5/8
Stabilizing ring	SR-19-16
Labyrinth ring	2 x LOR 43
PosiTrac Plus contact element	2 x B10724-44
End plug (suffix Y)	EPR 8
Max. speed for PosiTrac Plus seal	2150 r/min
P60°	92.5 kN
P90°	55.6 kN
P120°	33.8 kN
P150°	30.7 kN
P180°	36.9 kN
Pa	14 kN
Mass pillow block	32.2 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	515.2 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.625 in
Initial grease fill	181.44 g