

INA 81224-TV thrust roller bearings

How do you find the INA 81224-TV thrust roller bearings 80 mm Shaft Size specification? Manufacturers Online Free check
Mounted Bearing Engineering Group

| | |
|--------------------------|-------------------------|
| Engineering Group | Mounted Bearing |
| Shaft Size | 80 mm |
| Shaft Size Type | Metric |
| Full Timken Part Number | QVVK20V080SB |
| Locking Style | Double V-Lock |
| Weight | 35 lb |
| Housing Style | Four-Bolt Square Flange |
| UPC Code | 0883450363181 |
| Dimension BC | 11.75 in |
| Dimension C | 4.9 in |
| Dimension D | 8.5000 in |
| Dimension E | 8.31 in |
| Dimension F | 10.56 in |
| Dimension H | 1.50 in |
| Dimension J (Bolt Size) | 0.875 in |
| Dimension L Exp | 4.54 in |
| Dimension L Fix | 4.46 in |
| Dimension N | 4.060 in |
| Dimension RVV | 0.16 in |
| Dimension SVV | 4.62 in |
| C – Dynamic Load (Basic) | 97700 lb |
| C0 – Static Load | 113000 lb |

| | |
|-------------------------------------|-----------|
| e – Geometry Factor | 0.26 |
| Y1 – Geometry Factor | 2.84 |
| Y2 – Geometry Factor | 4.23 |
| Oil Lubrication – M/N Seal | 1200 rpm |
| Oil Lubrication – T Seal | 2000 rpm |
| Oil Lubrication – B/C/O Seal | 900 rpm |
| Grease Lubrication – M/N Seal | 1200 rpm |
| Grease Lubrication – T Seal | 1600 rpm |
| Grease Lubrication – B/C/O Seal | 900 rpm |
| Float | 0.083 in |
| Shaft Tolerance | 0.0030 in |
| Eng Internal Radial Clearance – Min | 0.0043 |
| Eng Internal Radial Clearance – Max | 0.0055 |
| Pre Install Clearance Min | 0.0043 in |
| Pre Install Clearance Max | 0.0055 in |