

INA B8 thrust ball bearings

Various types and sizes to accommodate your INA B8 thrust ball bearings 0.0 Inventory requirements.

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.032
EAN	7316577001887
Product Group	B04286
Stud Profile	Female
Mounting Thread	M6 X 1
Thread Direction	Left Hand
Rolling Element	Spherical Plain
Material – Outer Member	Steel
Material – Ball	Steel
Material – Liner	Plastic Teflon
Relubricatable	No
Enclosure	Open
Other Features	2 Piece Zinc Plated Outer Self Lubricating Maintenance Free
Long Description	6MM Bore; 6.75MM House Width; Female Stud Profile; M6 X 1; Left Hand Thread Direction; Spherical Pla
Inch – Metric	Metric
UNSPSC	31171508
Harmonized Tariff Code	8483.30.80.55

Noun	Bearing
Keyword 3	Rod End
Keyword String	Plain Spherical Rod End
Manufacturer Item Number	SILKB 6 F
Weight / LBS	0.062
Housing Width	0.266 Inch 6.75 Millimeter
d	6 mm
Ball Width	0.354 Inch 9 Millimeter
bore diameter:	6 mm
ball material:	Steel
misalignment angle:	13 °
race material:	PTFE Composite
shank thread length:	9 mm
radial static load capacity:	6.8 kN
rod end type:	Female Threaded
operating temperature range:	-40 to +75 °F
shank thread size:	M6
head diameter:	21 mm
thread direction:	Left Hand
head width:	6.75 mm
grade:	Commercial/Industrial
ball width:	9 mm
lubrication type:	Maintenance Free/Self-Lubricating
length to ball center:	30 mm
housing material:	Zinc-Plated Steel
standards met:	ISO 12240-4:1998, ISO 965-1:1998
d2 max.	21 mm

B	9 mm
G	M 6
C1 max.	7.5 mm
h1	30 mm
α	13 °
dk	12.7 mm
d3 ≈	10 mm
d4 max.	14 mm
l3 min.	9 mm
l4 max.	42 mm
l5 ≈	5 mm
l7 min.	11 mm
w	10 mm
r1 min.	0.3 mm
Basic dynamic load rating C	4.25 kN
Basic static load rating C0	6.8 kN
Specific dynamic load factor K	50 N/mm ²
Material constant KM	530
Mass rod end	0.028 kg