

# INA BCE610 needle roller bearings

Find the discount INA BCE610 needle roller bearings N/A Minimum Buy Quantity online you need . We offer ... If you check 0.0 Inventory out our large selection of INA BCE610 needle roller bearings once .

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	28.15
EAN	7316576668951
Product Group	M06288
Number of Mounting Holes	2
Mounting Method	Tapered Adapter Sleeve
Housing Style	2 Bolt Pillow Block
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Expansion
Mounting Bolts	7/8 Inch
Relubricatable	Yes
Insert Part Number	22220 CCK/W33
Seals	Labyrinth
Housing Configuration	2 Piece Split
Inch – Metric	Inch
Other Features	Double Row   Heavy Duty

Long Description	2 Bolt Pillow Block; 3-7/16" Bore; 4-1/2" Base to Center Height; Tapered Adapter Sleeve Mo
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	SAF 22520
Weight / LBS	62
Nominal Bolt Center to Center	11.9 Inch   302.3 Millimeter
Actual Bolt Center to Center	0 Inch   0Millimeter
Bolt Spacing Maximum	13.125 Inch   333.375Millimeter
d	3.438 Inch   87.325 Millimeter
D	6.125 Inch   155.575 Millimeter
B	4.5 Inch   114.3 Millimeter
Bolt Spacing Minimum	11.625 Inch   295.275Millimeter
da	87.313 mm
Da	180 mm
Ca	55.804 mm
A1	111.125 mm
A2	152.797 mm
S	4.763 mm
ba	44.45 mm
H	217.488 mm
H1	114.3 mm
H2	44.45 mm
J min.	295.275 mm
J max.	333.375 mm

L	387.35 mm
N1	25.4 mm
R1	58.737 mm
R2	30.163 mm
RG	3/8 NPT
PG	1/4 NPT
h	42.069 mm
Housing	SAF 520
Bearing	22220 EK
Adapter sleeve assembly	SNW 20×3.7/16
Stabilizing ring	SR-20-17
Labyrinth ring	2 x LOR 102
End plug (suffix Y)	EPR 12
Bearing limiting speed	4500 r/min
P60°	136 kN
P90°	81.4 kN
P120°	50.7 kN
P150°	46.3 kN
P180°	55.6 kN
Pa	13.8 kN
Mass pillow block	28.1 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.875 in
Initial grease fill	181.44 g