

INA BXRE211-2RSR needle roller bearings

170 Million used INA BXRE211-2RSR needle roller bearings instantly searchable. Shop our large selection of parts based on brand, price, description, and location. Order the 30 mm d with stock ...

d	30 mm
D	55 mm
B	13 mm
rs min	1 mm
Radial clearance class	C3
Mass	0.12 kg
Dynamic load, C	13.2 kN
Static load, C0	8.3 kN
Fatigue limit load, Cu	0.38 kN
f0	14.8
Nlim (grease)	7,700 rpm
Min operating temperature, Tmin	-25 °C
Max operating temperature, Tmax	110 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	5.85 Hz
Characteristic outer ring frequency, BPF0	4.59 Hz
Characteristic inner ring frequency, BRFI	6.41 Hz
da min	35 mm

da max	37 mm
Da max	50 mm
ra max	1 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	0692314580738
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C3-Loose
Inch – Metric	Metric
Long Description	30MM Bore; 55MM Outside Diameter; 13MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No
Other Features	Deep Groove Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68

Noun	Bearing
Keyword String	Ball
Weight / LBS	0.256
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.512 Inch 13 Millimeter
Outside Diameter	2.165 Inch 55 Millimeter
Bore	1.181 Inch 30 Millimeter