

INA BXRE307-2RSR needle roller bearings

What is 0.0 Inventory the best place to buy INA BXRE307-2RSR needle roller bearings online? Manufacturing Service .

| | |
|---------------------------|-----------------------------------------------------------------------------------------------|
| Inventory | 0.0 |
| Manufacturer Name | TIMKEN |
| Minimum Buy Quantity | N/A |
| Weight | 4.185 lb |
| EAN | 0087796265585 |
| Product Group | M06110 |
| Number of Mounting Holes | 2 |
| Mounting Method | Set Screw |
| Housing Style | 2 Bolt Pillow Block |
| Rolling Element | Ball Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Non-expansion |
| Mounting Bolts | 12 Millimeter |
| Relubricatable | Yes |
| Insert Part Number | GYE35KRRB |
| Seals | Double Land Riding Rubber Contact |
| Housing Configuration | 1 Piece Solid |
| Inch – Metric | Metric |
| Other Features | Single Row Spherical Normal Duty High Base Black Housing Powder Coated Epoxy Finish |

| | |
|-------------------------------|------------------------------------------------------------------------------------------------------|
| Long Description | 2 Bolt Pillow Block; 35MM Bore; 47.6MM Base to Center Height; Set Screw Mount; Ball Bearing; 105.6MM |
| UNSPSC | 31171511 |
| Harmonized Tariff Code | 8483.20.40.40 |
| Noun | Bearing |
| Keyword String | Pillow Block |
| Manufacturer Item Number | YAS 35 SGT |
| Weight / LBS | 3.846 |
| Nominal Bolt Center to Center | 5 Inch 127 Millimeter |
| Bolt Spacing Minimum | 4.157 Inch 105.6Millimeter |
| Actual Bolt Center to Center | 0 Inch 0Millimeter |
| D | 1.689 Inch 42.9 Millimeter |
| B | 1.874 Inch 47.6 Millimeter |
| Bolt Spacing Maximum | 6.094 Inch 154.8Millimeter |
| d | 1.378 Inch 35 Millimeter |
| Shaft Size d | 1.378 in |
| Bearing Type | Ball Bearing |
| Inside Ring Outside Diameter | 1.844 in |
| Dimension T | 0.921 in |
| Dimension D1 | 1.843 in |
| Series | Industrial |
| Seal Type | Shroud Seal |
| Base to Center Height H | 47.63 mm |
| Total Length L | 166.7 mm |
| Total Width A | 1.843 in |
| Bolt Hole Spacing J | 130.2 mm |
| Bolt Hole Width N | 14.3 mm |

| | |
|------------------------------|-------------------------------------|
| Bolt Hole Length N1 | 24.6 mm |
| Foot Height H1 | 18.3 mm |
| Total Height H2 | 95.3 mm |
| Dimension L1 | 55.6 mm |
| Inside Ring Width B | =Bearings1_Inside Ring Width= mm |
| Center of Bearing from End S | 17 mm |
| Dimension B1 | 1.780 in |
| Static Load Rating | 3440 lbf |
| Dynamic Load Rating | 6400 lbf |