

INA C364224 needle roller bearings

Find the discount INA C364224 needle roller bearings online you 55x30x13 Size (mm) need . We offer ... If you check out 55 Bore Diameter (mm) our large selection of INA C364224 needle roller bearings once .

Size (mm)	55x30x13
Bore Diameter (mm)	55
Outer Diameter (mm)	30
Width (mm)	13
d	30 mm
D	55 mm
B	13 mm
d1	38.2 mm
D2	49 mm
D3	52.6 mm
b	1.35 mm
C	2.06 mm
r0	0.4 mm
r1,2 – min.	1 mm
da – min.	34.6 mm
Da – max.	50.4 mm
Db – min.	62 mm
ba – min.	1.5 mm
Ca – max.	3.18 mm
ra – max.	1 mm
Basic dynamic load rating – C	13.8 kN

Basic static load rating – C0	8.3 kN
Fatigue load limit – Pu	0.355 kN
Reference speed	28000 r/min
Limiting speed	17000 r/min
Calculation factor – kr	0.025
Calculation factor – f0	14.7
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.111
EAN	7316571409931
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	Yes
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	30MM Bore; 55MM Outside Diameter; 13MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Fil
Other Features	Deep Groove With Snap Ring Groove
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing

Keyword String	Ball
Weight / LBS	0.26
Bore	1.181 Inch 30 Millimeter
Outer Race Width	0.512 Inch 13 Millimeter
Outside Diameter	2.165 Inch 55 Millimeter
Inner Race Width	0 Inch 0 Millimeter
d1 ≈	38.2 mm
D2 ≈	49 mm
r0 max.	0.4 mm
da min.	34.6 mm
Da max.	50.4 mm
Db min.	62 mm
ba min.	1.5 mm
Ca max.	3.18 mm
ra max.	1 mm
Basic dynamic load rating C	13.8 kN
Basic static load rating C0	8.3 kN
Fatigue load limit Pu	0.355 kN
Calculation factor kr	0.025
Calculation factor f0	14.7
Mass bearing	0.12 kg