

INA C364224 needle roller bearings

Find the discount INA C364224 needle roller bearings online you 55x30x13 Size (mm) need . We offer ... If you check out 55 Bore Diameter (mm) our large selection of INA C364224 needle roller bearings once .

| | |
|-------------------------------|----------|
| Size (mm) | 55x30x13 |
| Bore Diameter (mm) | 55 |
| Outer Diameter (mm) | 30 |
| Width (mm) | 13 |
| d | 30 mm |
| D | 55 mm |
| B | 13 mm |
| d1 | 38.2 mm |
| D2 | 49 mm |
| D3 | 52.6 mm |
| b | 1.35 mm |
| C | 2.06 mm |
| r0 | 0.4 mm |
| r1,2 – min. | 1 mm |
| da – min. | 34.6 mm |
| Da – max. | 50.4 mm |
| Db – min. | 62 mm |
| ba – min. | 1.5 mm |
| Ca – max. | 3.18 mm |
| ra – max. | 1 mm |
| Basic dynamic load rating – C | 13.8 kN |

| | |
|---------------------------------|--|
| Basic static load rating – C0 | 8.3 kN |
| Fatigue load limit – Pu | 0.355 kN |
| Reference speed | 28000 r/min |
| Limiting speed | 17000 r/min |
| Calculation factor – kr | 0.025 |
| Calculation factor – f0 | 14.7 |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.111 |
| EAN | 7316571409931 |
| Product Group | B00308 |
| Enclosure | Open |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | Yes |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C0-Medium |
| Inch – Metric | Metric |
| Long Description | 30MM Bore; 55MM Outside Diameter; 13MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Fil |
| Other Features | Deep Groove With Snap Ring Groove |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |

| | |
|-----------------------------|----------------------------|
| Keyword String | Ball |
| Weight / LBS | 0.26 |
| Bore | 1.181 Inch 30 Millimeter |
| Outer Race Width | 0.512 Inch 13 Millimeter |
| Outside Diameter | 2.165 Inch 55 Millimeter |
| Inner Race Width | 0 Inch 0 Millimeter |
| d1 ≈ | 38.2 mm |
| D2 ≈ | 49 mm |
| r0 max. | 0.4 mm |
| da min. | 34.6 mm |
| Da max. | 50.4 mm |
| Db min. | 62 mm |
| ba min. | 1.5 mm |
| Ca max. | 3.18 mm |
| ra max. | 1 mm |
| Basic dynamic load rating C | 13.8 kN |
| Basic static load rating C0 | 8.3 kN |
| Fatigue load limit Pu | 0.355 kN |
| Calculation factor kr | 0.025 |
| Calculation factor f0 | 14.7 |
| Mass bearing | 0.12 kg |