

# INA CSXU 050.2RS angular contact ball bearings

We work closely with our INA CSXU 050.2RS angular contact ball bearings manufacturing partners to bring the 0.0 Inventory best value to customers.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 27.694   |
| EAN                       | 0883450295437  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 6  |
| Mounting Method           | V Lock   |
| Housing Style             | 6 Bolt Round Flange Cartridge  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Expansion  |
| Mounting Bolts            | 3/4 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22226  |
| Seals                     | Triple Lip Nitrile Rubber  |
| Housing Configuration     | 1 Piece Solid  |
| Pilot Configuration       | With Pilot   |
| Inch – Metric             | Inch   |
| Long Description          | 6 Bolt Round Flange Cartridge;<br>4-7/16" Bore; 11.8" Bolt<br>Circle; 5-7/8" Bolt Spacing; |

|                                       |                                    |
|---------------------------------------|------------------------------------|
| Other Features                        | Double Row   Single Nut            |
| UNSPSC                                | 31171501                           |
| Harmonized Tariff Code                | 8483.20.40.80                      |
| Noun                                  | Bearing                            |
| Keyword String                        | Flanged                            |
| Weight / LBS                          | 72                                 |
| D                                     | 5.82 Inch   147.828 Millimeter     |
| Cartridge Pilot Diameter              | 10.25 Inch   260.35 Millimeter     |
| Cartridge Pilot Depth                 | 1.9 Inch   48.26 Millimeter        |
| Bolt Spacing                          | 5.875 Inch   149.225<br>Millimeter |
| Nominal Bolt Circle Diameter<br>Round | 11.8 Inch   300 Millimeter         |
| d                                     | 4.438 Inch   112.725<br>Millimeter |