

# INA DL15 thrust ball bearings

Question INA DL15 thrust ball bearings ? 105.816 mm Ca Find what you need faster by entering your 133.35 mm da information

da	133.35 mm
Da	269.999 mm
Ca	105.816 mm
A1	158.75 mm
A2	215.9 mm
S	4.763 mm
ba	77.787 mm
H	317.5 mm
H1	160.35 mm
H2	63.5 mm
J min.	431.8 mm
J max.	463.55 mm
J1	95.25 mm
L	539.75 mm
N1	28.575 mm
R1	95.25 mm
R2	39.688 mm
RG	3/8 NPT
PG	1/4 NPT
h	50.8 mm
Housing	SAW 530
Bearing	23230 CCK/W33
Adapter sleeve assembly	SNW 130×5.1/4

Stabilizing ring	SR-30-0
Labyrinth ring	2 x LOR 126
End plug (suffix Y)	EPR 16
Bearing limiting speed	2200 r/min
P60°	230 kN
P90°	138 kN
P120°	87.2 kN
P150°	80.1 kN
P180°	96.1 kN
Pa	43.2 kN
Mass pillow block	92.5 kg
Cap bolt	4 x 3/4-10 UNC
Cap bolt recommended tightening torque	359.3 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	623.7 g