

# INA EGB4550-E40-B plain bearings

Request A Quote For Your Special INA EGB4550-E40-B plain bearings Needs Today! Free Quotes. ISO 30 mm A 9001 certified.

|        |          |
|--------|----------|
| A      | 30 mm    |
| A1     | 18 mm    |
| B      | 19.1 mm  |
| B1     | 28.6 mm  |
| d      | 15 mm    |
| d1     | 27.2 mm  |
| Dz     | 46 mm    |
| E      | 10 mm    |
| G      | M6x1     |
| H      | 30.2 mm  |
| H1     | 9 mm     |
| H2     | 57 mm    |
| J      | 47 mm    |
| L      | 63 mm    |
| L1     | 17.5 mm  |
| N      | M8       |
| s1     | 23.05 mm |
| S      | 6.5 mm   |
| Z      | 57.9 mm  |
| C      | 9.55 kN  |
| C0     | 4.78 kN  |
| T min. | -20 °C   |
| T max. | 200 °C   |

|   |            |
|---|------------|
| Weight                                      | 0.49 kg    |
| Recommended tightening torque for set screw | 5.5 Nm     |
| Designation of housing                      | PAE203N-   |
| Designation of bearing                      | ES202G2T20 |
| Designation of closed end cover             | SCCE203    |
| Designation of open end cover               | SCOE202-15 |