

INA EGW16 - E40 - B plain bearings

We work closely with our INA EGW16-E40-B plain bearings manufacturing 0.0 Inventory partners to bring the best value to customers. N/A Minimum Buy Quantity

| | |
|-------------------------|--|
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 1.559 |
| EAN | 7316576625831 |
| Product Group | B00152 |
| Mounting Method | Tapered Adapter |
| Enclosure | Open |
| Rolling Element | Ball Bearing |
| Adapter Sleeve | H-311 |
| Cage Material | Polyamide |
| Precision Class | ABEC 1 ISO P0 |
| Internal Clearance | C3-Loose |
| Number of Rows of Balls | Double Row |
| Other Features | Allowable Misalignment 3 Deg High Capacity Design 1:12 Taper |
| Long Description | 55MM Bore; Tapered Adapter Mount; 120MM Outside Diameter; 29MM Inner Race Width; 29MM Outer Race Wid |
| Inch – Metric | Metric |
| UNSPSC | 31171532 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |

| | |
|--------------------------|-----------------------------|
| Keyword String | Self Aligning |
| Manufacturer Item Number | 1311 EKTN9/C3 |
| Weight / LBS | 3.433 |
| D | 4.724 Inch 120 Millimeter |
| Inner Race Width | 1.142 Inch 29 Millimeter |
| Outer Race Width | 1.142 Inch 29 Millimeter |
| d | 2.165 Inch 55 Millimeter |
| bore diameter: | 55 mm |
| precision rating: | Not Rated |
| outside diameter: | 120 mm |
| maximum rpm: | 7500 RPM |
| overall width: | 29 mm |
| cage material: | Fiberglass Reinforced Nylon |
| bore type: | Tapered 1:12 |
| finish/coating: | Uncoated |
| closure type: | Open |
| maximum misalignment: | 3 ° |
| internal clearance: | C3 |
| outer ring width: | 29 mm |
| dynamic load capacity: | 50.7 kN |
| fillet radius: | 2 mm |
| static load capacity: | 18 kN |
| series: | 1300 |