

INA F-91551 plain bearings

170 Million 180 mm Da used INA F-91551 plain bearings instantly searchable. Shop our large selection of parts based on brand, price, description, and location. Order the with 55.804 mm Ca stock ... 88.9 mm da

da	88.9 mm
Da	180 mm
Ca	55.804 mm
A1	111.125 mm
A2	222.25 mm
S	4.763 mm
ba	44.45 mm
H	217.488 mm
H1	114.3 mm
H2	44.45 mm
J min.	295.275 mm
J max.	333.375 mm
J1	60.325 mm
L	387.35 mm
N1	22.225 mm
R1	58.737 mm
R2	30.163 mm
RG	3/8 NPT
PG	1/4 NPT
h	42.069 mm
Housing	FSAF 520
Bearing	22220 EK
Adapter sleeve assembly	SNW 20×3.1/2

Stabilizing ring	SR-20-17
Taconite seal	TER 103
End plug (suffix Y)	EPR 15
Max. speed for Taconite seal	900 r/min
P60°	119 kN
P90°	71.2 kN
P120°	44.5 kN
P150°	40 kN
P180°	48.9 kN
Pa	13.8 kN
Mass pillow block	28.1 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.75 in
Initial grease fill	181.44 g