

INA GE 120 D0 plain bearings

What are the types of INA GE 120 D0 plain bearings ?
Manufacturing Service . Get Your Free, 168.275 mm db Instant price, design review. 150 mm da

da	150 mm
db	168.275 mm
dc	146.05 mm
Da	269.999 mm
Ca	105.816 mm
A1	158.75 mm
A2	238.125 mm
S	4.763 mm
ba	77.787 mm
H	317.5 mm
H1	160.35 mm
H2	63.5 mm
J min.	431.8 mm
J max.	463.55 mm
J1	95.25 mm
L	539.75 mm
N1	28.575 mm
R1	95.25 mm
R2	39.688 mm
RG	3/4 NPT
PG	1/4 NPT
h	50.8 mm
Housing	SAW 230

Bearing	23230 CC/W33
Lock nut	AN 30
Lock washer	W 30
Stabilizing ring	SR-30-0
Labyrinth ring (db shaft position)	LOR 151
PosiTrac Plus contact element (db shaft position)	B10724-151
Labyrinth ring (dc shaft position)	LOR 134
PosiTrac Plus contact element (dc shaft position)	B10724-134
End plug (suffix Y)	EPR 17
Max. speed for PosiTrac Plus seal	850 r/min
P60°	230 kN
P90°	138 kN
P120°	87.2 kN
P150°	80.1 kN
P180°	96.1 kN
Pa	43.2 kN
Mass pillow block	92.5 kg
Cap bolt	4 x 3/4-10 UNC
Cap bolt recommended tightening torque	359.3 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	623.7 g