

INA GE160-AX plain bearings

Online shopping 68 Outer Diameter (mm) INA GE160-AX plain bearings 45 Bore Diameter (mm) from a great selection 45x68x12 Size (mm) at Store. ... Accessories.

Size (mm)	45x68x12
Bore Diameter (mm)	45
Outer Diameter (mm)	68
Width (mm)	12
d	45 mm
D	68 mm
B	12 mm
C	12 mm
r min.	0,6 mm
da min.	49 mm
da max	50 mm
Da max.	64 mm
ra max.	0,6 mm
Weight	0,126 Kg
Basic dynamic load rating (C)	14,1 kN
Basic static load rating (C0)	10,9 kN
(Grease) Lubrication Speed	5 600 r/min
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	0.12
EAN	0029176377174
Product Group	B00308

Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	45MM Bore; 68MM Outside Diameter; 12MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No
Other Features	Deep Groove Rubber Seal
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6909DDU
Weight / LBS	0.2778
Inner Race Width	0 Inch 0 Millimeter
Bore	1.772 Inch 45 Millimeter
Outer Race Width	0.472 Inch 12 Millimeter
Outside Diameter	2.677 Inch 68 Millimeter
SRI	3.49
hidYobi	6909DDU
LangID	1
D_	68
SREX	0.02

B_	12
da min	49
hidTable	ecat_NSRDGB
SRE	3.49
mass	0.126
GRS rpm	5600
ra	0.6
SRIX	0.02
D_a	64
SRIN	-0.02
C0	10.9
fo	15.9
SREN	-0.02
DE_	63.247
Prod_Type3	DGBB_SR_DD
DA_	6.747
bomp	0
Z_	15
yobi	6909DDU
C_conv	14100
ALPHA_	0
SDM_	56.5
r	0.6
KBRG	6161
SBRG	19
DI_	49.753