

INA GF 60 D0 plain bearings

Shop INA GF 60 D0 plain bearings huge online discount inventory. and Import machinery parts 109.537 mm da your car 200 mm Da needs with Free Shipping and Free Extended Warranty.

da	109.537 mm
Da	200 mm
Ca	62.789 mm
A1	120.65 mm
A2	231.775 mm
ba	51.594 mm
H	244.475 mm
H1	125.425 mm
H2	52.388 mm
J min.	320.675 mm
J max.	368.3 mm
J1	69.85 mm
L	419.1 mm
N1	24.209 mm
R1	73.025 mm
R2	31.75 mm
RG	3/8 NPT
PG	1/4 NPT
h	40.922 mm
Housing	SAFS 026 KA
Bearing	23026 CCK/W33
Adapter sleeve assembly	SNW 3026×4.5/16
Stabilizing ring	2 x 38151-26

Taconite seal	TER 115
End plug (suffix Y)	EPR 15
Max. speed for Taconite seal	700 r/min
P60°	178 kN
P90°	107 kN
P120°	66.7 kN
P150°	59.6 kN
P180°	72.5 kN
Pa	20.2 kN
Mass pillow block	50.8 kg
Cap bolt	5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	0.75 in
Initial grease fill	232.47 g