

INA GIKR 8 PB plain bearings

Various 19 Outer Diameter (mm) types and sizes to 15 Bore Diameter (mm) accommodate your INA GIKR 8 PB plain bearings requirements.

Bore Diameter (mm)	15
Outer Diameter (mm)	19
Fw	15 mm
Ew	19 mm
Bc	13 mm
Weight	0.007 Kg
Basic dynamic load rating (C)	9.66 kN
Basic static load rating (C0)	12.6 kN
(Grease) Lubrication Speed	18000 r/min
(Oil) Lubrication Speed	28000 r/min
Inventory	238.0
Manufacturer Name	KOYO
Minimum Buy Quantity	N/A
Weight / Kilogram	0.012
EAN	0060579021295
Product Group	B04144
Rolling Element	Needle Roller Bearing
Component	Roller Assembly Only
Enclosure	Not Applicable
Self Aligning	No
Retainer	Yes
Number of Rows of Rollers	Single Row
Separable	No

Closed End	Not Applicable
Inch – Metric	Metric
Thrust Bearing	No
Long Description	15MM Bore; 19MM Outside Diameter; 13MM Width; Needle Roller Bearing; Roller Assembly Only; No Self A
Other Features	Radial Roller Steel Cage
UNSPSC	31171512
Harmonized Tariff Code	8482.40.00.00
Noun	Bearing
Keyword String	Needle
Manufacturer Item Number	K15X19X13
Weight / LBS	0.015
Outside Diameter	0.748 Inch 19 Millimeter
Width	0.512 Inch 13 Millimeter
Bore	0.591 Inch 15 Millimeter
Bearing No.	K15X19X13
Cr	9.66
C0r	12.6
Cu	1.90
Grease lub.	18000
Oil lub.	28000
P/S	S
(Refer.)Mass(kg)	0.007
Shaft(max.)	15.000
Shaft(min.)	14.992
Housing(max.)	19.020
Housing(min.)	19.007