

INA GIPR 30 PW plain bearings

are a few brands you will find in our inventory. Find 180x280x100 Size (mm) INA GIPR 30 PW plain bearings to see what's in stock!

Size (mm)	180x280x100
Bore Diameter (mm)	180
Outer Diameter (mm)	280
Width (mm)	100
d	180 mm
D	280 mm
B	100 mm
C	100 mm
r min.	2,1 mm
da min.	192 mm
da max	200 mm
Da min	245 mm
Da max.	268 mm
ra max.	2 mm
Weight	22,7 Kg
Basic dynamic load rating (C)	965 kN
Basic static load rating (C0)	1750 kN
(Grease) Lubrication Speed	950 r/min
(Oil) Lubrication Speed	1200 r/min
Calculation factor (e)	0,32
Calculation factor (Y0)	2
Calculation factor (Y2)	3,1
Inventory	0.0

Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	22.5
EAN	0029176037177
Product Group	B04311
Internal Clearance	C0-Medium
Mounting Method	Shaft Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Straight
Cage Material	Steel
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	Not Applicable
Inch – Metric	Metric
Long Description	180MM Straight Bore; 280MM Outside Diameter; 100MM Width; C0-Medium Clearance; Shaft Mount; Double R
UNSPSC	31171510
Harmonized Tariff Code	84823080
Noun	Bearing
Keyword String	Spherical
Manufacturer Item Number	24036CE4
Weight / LBS	22.5
Adapter Part Number	Not Applicable Inch Not Applicable Millimeter
Outside Diameter	11.024 Inch 280 Millimeter
Bore	7.087 Inch 180 Millimeter
Width	3.937 Inch 100 Millimeter

Y3	2.1
hidYobi	24036CE4
LangID	1
Y1	2.1
D_	280
Y2	3.1
Macha rpm	0
B_	100
da min	192
hidTable	ecat_NSSPHR
Oil rpm	1200
Y0	2
mass	22.7
GRS rpm	950
ra	2
TSR rpm	1500
C0	1750
DE_	256.115
X0	1
Prod_Type3	SRB_CTB_CB
X1	1
X2	0.67
SIR	40
e	0.32
DA_	25.5
bomp	24036CE4
Z_	23
ALP2	10
ALP1	12

ALP3	0
D_a max	268
D_a min	245
yobi	24036CE4
ALPHA_	0.212
SDM_	231.188
r	2.1
KBRG	2322
SBRG	40
DI_	206.261