## INA GIR 12 DO plain bearings

INA GIR 12 DO plain bearings Engineering Calculator , Manufacturing Service . 2.1875 in d Get Your Free.

| d                             | 2.1875 in   |
|-------------------------------|---|
| D                             | 9-1/4 to 10-1/4 in  |
| overall length:               | 12.0000 in  |
| base width:                   | 4 in  |
| overall height:               | 8.0000 in   |
| expansion type:               | Non-Expansion Bearing (Fixed)   |
| mounting:                     | Two-Bolt Base   |
| finish/coating:               | Black Oxide   |
| bearing type:                 | Tapered Roller  |
| В                             | 5-3/4 in  |
| bore type:                    | Round   |
| seal type:                    | Labyrinth   |
| housing construction:         | Split Pillow Block  |
| radial dynamic load capacity: | 2100 lb   |
| base to bore centerline:      | 3.7500 in   |
| maximum rpm:                  | 2000 RPM  |
| duty type:                    | Heavy Duty  |
| lubrication type:             | Lubrication Fitting   |
| housing material:             | Cast Iron   |
| standards met:                | UL, AFBMA, AGMA, ASMMA, ASTM<br>A48 Class 30, BSA, CMA, MPTA,<br>PTDA |
| locking device:               | Concentric Collar   |
| manufacturer catalog number:  | 065293  |
|                               | <del>-</del>  |