

# INA GK 17 D0 plain bearings

offers a INA GK 17 D0 plain bearings selection of Genuine at Wholesale Prices. We are a INA GK 17 D0 plain bearings Certified Parts 0.0 Inventory Retailer

Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	220.64
EAN	0087796312166
Product Group	B04311
Internal Clearance	C0-Medium
Mounting Method	Adapter Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Tapered
Cage Material	Bronze
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	AHX30/500 A0H30/500 (Specify Bore)
Withdrawal Nut	HM30/500
Inch – Metric	Metric
Long Description	500MM Tapered Bore; 720MM Outside Diameter; 167MM Width; C0-Medium Clearance; Adapter Mount Mount; D

Other Features	Single Piece Cage   Finger Type   Land Piloted   Lubrication Groove and Holes in Outer Ring   Tapped
UNSPSC	31171510
Harmonized Tariff Code	8482.30.00.80
Noun	Bearing
Keyword String	Spherical
Manufacturer Item Number	230/500KYMBW507C08
Weight / LBS	486
D	28.346 Inch   720 Millimeter
d	19.685 Inch   500 Millimeter
Adapter Part Number	SNW30/500 (Specify Bore) Inch   H30/500 0H30/500H (Specify Bore) Millimeter
B	6.575 Inch   167 Millimeter
Design Unit	METRIC
Bore Taper	1/12
Bearing Weight	222 Kg
Cage Type	YMB
UPC Code	087796312166
d – Bore	500.000 mm
D – Outer Diameter	720.000 mm
B – Inner Ring Width	167 mm
B – Outer Ring Width	167.000 mm
R – Inner Ring To Clear Radius1	5.000 mm
r – Outer Ring To Clear Radius2	5.000 mm
da – Inner Ring Backing Diameter	550.000 mm

Da – Outer Ring Backing Diameter	673.000 mm
C0 – Static Radial Rating	8160000 N
C1(2) – Dynamic Radial Rating (Two-Rows)	4290000 N
e – ISO Factor <sup>3</sup>	0.21
Y0 – ISO Factor <sup>4</sup>	3.26
Y1 – ISO Factor <sup>5</sup>	4.85
Y2 – ISO Factor <sup>6</sup>	3.18
Reference Thermal Speed Rating (Grease)	510
Reference Thermal Speed Rating (Oil) <sup>7</sup>	580
Cg – Geometry Factor <sup>8</sup>	0.1037