## INA GRA108-NPP-B-AS2/V deep groove ball bearings

Enjoy High Margins on Competitive Pricing.Great 5 in Shaft Size Wholesale Products at Mounted Bearing Engineering Group Imperial Shaft Size Type Low Costs.

| Engineering Group       | Mounted Bearing         |
|-------------------------|-------------------------|
| Shaft Size              | 5 in                    |
| Shaft Size Type         | Imperial                |
| Full Timken Part Number | 99999B                  |
| Locking Style           | Single V-Lock           |
| Weight                  | 115 lb                  |
| Housing Style           | Four-Bolt Square Flange |
| UPC Code                | 0883450338905           |
| Dimension BC            | 12.88 in                |
| Dimension C             | 6.88 in                 |
| Dimension D             | 11.190 in               |
| Dimension E             | 7.000 in                |
| Dimension F             | 16.5 in                 |
| Dimension H             | 1.50 in                 |
| Dimension J (Bolt Size) | 1.125 in                |
| Dimension G             | 10.375 in               |
| Dimension L Exp         | 5.62 in                 |
| Dimension L Fix         | 5.53 in                 |
| Dimension N             | 5.450 in                |
| Dimension RV            | 0.29 in                 |
| Dimension SV            | 5.82 in                 |
| C0 — Static Load        | 237000 lb               |

| C — Dynamic Load (Basic)            | 194000 lb |
|-------------------------------------|-----------|
| e – Geometry Factor                 | 0.26      |
| Y1 — Geometry Factor                | 2.62      |
| Y2 — Geometry Factor                | 3.89      |
| Oil Lubrication — M/N Seal          | 650 rpm   |
| Oil Lubrication — T Seal            | 1200 rpm  |
| Oil Lubrication — B/C/O Seal        | 350 rpm   |
| Grease Lubrication - M/N Seal       | 650 rpm   |
| Grease Lubrication – T Seal         | 900 rpm   |
| Grease Lubrication - B/C/O Seal     | 350 rpm   |
| Float                               | 0.083 in  |
| Shaft Tolerance                     | 0.0050 in |
| Eng Internal Radial Clearance – Min | 0.0063    |
| Eng Internal Radial Clearance – Max | 0.0079    |
| Pre Install Clearance Min           | 0.0063 in |
| Pre Install Clearance Max           | 0.0079 in |