

INA KSR16-L0-10-10-17-08 bearing units

Online shopping INA KSR16-L0-10-10-17-08 bearing units from 17 mm d a great selection at Store. ... Accessories.

d	17 mm
D	62 mm
B	17 mm
rs min	1.1 mm
Radial clearance class	C3
Mass	0.27 kg
Dynamic load, C	22.7 kN
Static load, C0	10.8 kN
Fatigue limit load, Cu	0.49 kN
f0	11.1
Nlim (oil)	16,000 rpm
Nlim (grease)	14,000 rpm
Min operating temperature, Tmin	-60 °C
Characteristic cage frequency, FTF	0.34 Hz
Characteristic rolling element frequency, BSF	2.79 Hz
Characteristic outer ring frequency, BPF0	2.04 Hz
Characteristic inner ring frequency, BRFI	3.96 Hz
da min	23.5 mm
Da max	55.5 mm
ra max	1 mm

Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.264
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C3-Loose
Inch – Metric	Metric
Long Description	17MM Bore; 62MM Outside Diameter; 17MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Fil
Other Features	Deep Groove
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.59965
Bore	0.669 Inch 17 Millimeter
Outside Diameter	2.441 Inch 62 Millimeter
Outer Race Width	0.669 Inch 17 Millimeter
Inner Race Width	0 Inch 0 Millimeter