

# INA KSR16-L0-12-10-13-16 bearing units

How do I place 0.0 Inventory an EMERGENCY order for a INA KSR16-L0-12-10-13-16 bearing units that I N/A Minimum Buy Quantity want to pick up at a our store? ABB MOTORS AND MECHANICAL INC Manufacturer Name

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | ABB MOTORS AND MECHANICAL INC   |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 87.589  |
| EAN                       | 0782475033881   |
| Product Group             | M06288  |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Concentric Collar   |
| Housing Style             | 4 Bolt Pillow Block   |
| Rolling Element           | Tapered Roller Bearing  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Expansion   |
| Mounting Bolts            | 7/8 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | S1U-DI-415  |
| Seals                     | Single Lip Contact  |
| Housing Configuration     | 2 Piece Split   |
| Inch – Metric             | Inch  |
| Other Features            | Double Row   Heavy Duty  <br>Optional E-Tect Seal   Double<br>Collar   With Set Screw |

|                               |  |
|-------------------------------|--|
| Long Description              | 4 Bolt Pillow Block; 4-15/16" Bore; 6-1/4" Base to Center Height; Concentric Collar Mount; |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.80  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | P4B-DI-415E WD DBL INTERLOCK   |
| Manufacturer Internal Number  | 060793   |
| Weight / LBS                  | 181  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |
| Bolt Spacing Maximum          | 18.063 Inch   458.8Millimeter  |
| B                             | 6.25 Inch   158.75 Millimeter  |
| Bolt Spacing Minimum          | 15.5 Inch   393.7Millimeter  |
| Nominal Bolt Center to Center | 16.8 Inch   426.7 Millimeter   |
| D                             | 7.25 Inch   184.15 Millimeter  |
| d                             | 4.938 Inch   125.425 Millimeter  |