

INA NA6915-ZW-XL needle roller bearings

Can't find what you're looking for INA NA6915-ZW-XL needle roller bearings ? Our 160 Outer Diameter (mm) expert 340x160x68 Size (mm) Representatives be in contact with you shortly!

| | |
|---|------------|
| Size (mm) | 340x160x68 |
| Bore Diameter (mm) | 340 |
| Outer Diameter (mm) | 160 |
| Width (mm) | 68 |
| d | 160 mm |
| D | 340 mm |
| B | 68 mm |
| d1 | 236.4 mm |
| D1 | 294.7 mm |
| r1,2 – min. | 4 mm |
| da – min. | 177 mm |
| Da – max. | 323 mm |
| ra – max. | 3 mm |
| Basic dynamic load rating – C | 276 kN |
| Basic dynamic load rating – effective – C _{eff} | 331 kN |
| Basic static load rating – C ₀ | 290 kN |
| Basic static load rating – effective – C _{0 eff} | 391 kN |
| Fatigue load limit – P _u | 7.6 kN |
| Reference speed | 5300 r/min |
| Limiting speed | 2800 r/min |

| | |
|---------------------------------|--|
| Calculation factor – kr | 0.03 |
| Calculation factor – f0 | 14.4 |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0 |
| Product Group | B00308 |
| Enclosure | Open |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | Silicon Nitride Rolling Element Electrical Insulated |
| Cage Material | Steel |
| Internal Clearance | C3-Loose |
| Inch – Metric | Metric |
| Long Description | 160MM Bore; 340MM Outside Diameter; 68MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No F |
| Other Features | Deep Groove Hybrid Silicon Nitride Rolling Element Wind Turbine Application |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Weight / LBS | 24 |

| | |
|---|------------------------------|
| Bore | 6.299 Inch 160 Millimeter |
| Outer Race Width | 2.677 Inch 68 Millimeter |
| Outside Diameter | 13.386 Inch 340 Millimeter |
| Inner Race Width | 0 Inch 0 Millimeter |
| d1 ≈ | 236.4 mm |
| D1 ≈ | 294.7 mm |
| r1,2 min. | 4 mm |
| da min. | 177 mm |
| Da max. | 323 mm |
| ra max. | 3 mm |
| Basic dynamic load rating C | 286 kN |
| Basic dynamic load rating – effective C | 348 kN |
| Basic static load rating C0 | 290 kN |
| Basic static load rating – effective C0 | 391 kN |
| Fatigue load limit Pu | 7.65 kN |
| Calculation factor kr | 0.03 |
| Calculation factor f0 | 14.4 |
| Mass bearing | 23.9 kg |