

INA NA6915-ZW-XL needle roller bearings

Can't find what you're looking for INA NA6915-ZW-XL needle roller bearings ? Our 160 Outer Diameter (mm) expert 340x160x68 Size (mm) Representatives be in contact with you shortly!

Size (mm)	340x160x68
Bore Diameter (mm)	340
Outer Diameter (mm)	160
Width (mm)	68
d	160 mm
D	340 mm
B	68 mm
d1	236.4 mm
D1	294.7 mm
r1,2 – min.	4 mm
da – min.	177 mm
Da – max.	323 mm
ra – max.	3 mm
Basic dynamic load rating – C	276 kN
Basic dynamic load rating – effective – C _{eff}	331 kN
Basic static load rating – C ₀	290 kN
Basic static load rating – effective – C _{0 eff}	391 kN
Fatigue load limit – P _u	7.6 kN
Reference speed	5300 r/min
Limiting speed	2800 r/min

Calculation factor – kr	0.03
Calculation factor – f0	14.4
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	Silicon Nitride Rolling Element Electrical Insulated
Cage Material	Steel
Internal Clearance	C3-Loose
Inch – Metric	Metric
Long Description	160MM Bore; 340MM Outside Diameter; 68MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No F
Other Features	Deep Groove Hybrid Silicon Nitride Rolling Element Wind Turbine Application
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	24

Bore	6.299 Inch 160 Millimeter
Outer Race Width	2.677 Inch 68 Millimeter
Outside Diameter	13.386 Inch 340 Millimeter
Inner Race Width	0 Inch 0 Millimeter
d1 ≈	236.4 mm
D1 ≈	294.7 mm
r1,2 min.	4 mm
da min.	177 mm
Da max.	323 mm
ra max.	3 mm
Basic dynamic load rating C	286 kN
Basic dynamic load rating – effective C	348 kN
Basic static load rating C0	290 kN
Basic static load rating – effective C0	391 kN
Fatigue load limit Pu	7.65 kN
Calculation factor kr	0.03
Calculation factor f0	14.4
Mass bearing	23.9 kg