

INA PASE5/8 bearing units

Request A Quote For Your Special INA PASE5/8 bearing units Needs Today! Free Quotes. ISO 9001 certified. 85 mm d

| | |
|---|-----------|
| d | 85 mm |
| D | 130 mm |
| B | 22 mm |
| rs min | 1.1 mm |
| Radial clearance class | CN |
| Mass | 0.89 kg |
| Dynamic load, C | 49.5 kN |
| Static load, C0 | 43 kN |
| Fatigue limit load, Cu | 1.89 kN |
| f0 | 15.8 |
| Nlim (grease) | 2,400 rpm |
| Min operating temperature, Tmin | -20 °C |
| Max operating temperature, Tmax | 80 °C |
| Characteristic cage frequency, FTF | 0.44 Hz |
| Characteristic rolling element frequency, BSF | 7.84 Hz |
| Characteristic outer ring frequency, BPF0 | 6.56 Hz |
| Characteristic inner ring frequency, BRFI | 8.44 Hz |
| da min | 91.5 mm |
| da max | 97 mm |
| Da max | 123.5 mm |
| ra max | 1 mm |

| | |
|---------------------------------|--|
| Inventory | 0.0 |
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.905 |
| Product Group | B00308 |
| Enclosure | 2 Seals |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Enclosure Type | Contact Seal |
| Internal Clearance | C0-Medium |
| Inch – Metric | Metric |
| Long Description | 85MM Bore; 130MM Outside Diameter; 22MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No |
| Other Features | Deep Groove Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C Prelubricated |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Weight / LBS | 1.96 |
| Bore | 3.346 Inch 85 Millimeter |

| | |
|------------------|-----------------------------|
| Outside Diameter | 5.118 Inch 130 Millimeter |
| Inner Race Width | 0 Inch 0 Millimeter |
| Outer Race Width | 0.866 Inch 22 Millimeter |