INA PASE50-N-FA125 bearing units

What are the dimensions of a INA PASE50-N-FA125 bearing units? Manufacturing Service Side Mount unit type: . Get Your Free, Instant Quote

unit type:Side Mountoverall length:4-1/6 inbearing type:Spherical Rolleroverall height:3-5/8 ind1.0000 inlubrication type:Lubrication Fittingslot spacing:3.0000 inmaximum rpm:3500 RPMslot width:0.5313 indynamic load capacity:11500 lbhousing material:Cast Ironexpansion type:Non-Expansion Bearing (Fixed)locking device:Set ScrewB3-5/8 inseal type:Labyrinthrod hole diameter:3/4 infinish/coating:Powder Coatedseries:B22400		
bearing type:Spherical Rolleroverall height:3-5/8 ind1.0000 inlubrication type:Lubrication Fittingslot spacing:3.0000 inmaximum rpm:3500 RPMslot width:0.5313 indynamic load capacity:11500 lbhousing material:Cast Ironexpansion type:Non-Expansion Bearing (Fixed)locking device:Set ScrewB3-5/8 inseal type:Labyrinthrod hole diameter:3/4 infinish/coating:Powder Coated	unit type:	Side Mount
overall height:3-5/8 ind1.0000 inlubrication type:Lubrication Fittingslot spacing:3.0000 inmaximum rpm:3500 RPMslot width:0.5313 indynamic load capacity:11500 lbhousing material:Cast Ironexpansion type:Non-Expansion Bearing (Fixed)locking device:Set ScrewB3-5/8 inseal type:Labyrinthrod hole diameter:3/4 infinish/coating:Powder Coated	overall length:	4-1/6 in
d1.0000 inlubrication type:Lubrication Fittingslot spacing:3.0000 inmaximum rpm:3500 RPMslot width:0.5313 indynamic load capacity:11500 lbhousing material:Cast Ironexpansion type:Non-Expansion Bearing (Fixed)locking device:Set ScrewB3-5/8 inseal type:Labyrinthrod hole diameter:3/4 infinish/coating:Powder Coated	bearing type:	Spherical Roller
lubrication type:Lubrication Fittingslot spacing:3.0000 inmaximum rpm:3500 RPMslot width:0.5313 indynamic load capacity:11500 lbhousing material:Cast Ironexpansion type:Non-Expansion Bearing (Fixed)locking device:Set ScrewB3-5/8 inseal type:Labyrinthrod hole diameter:3/4 infinish/coating:Powder Coated	overall height:	3-5/8 in
slot spacing:3.0000 inmaximum rpm:3500 RPMslot width:0.5313 indynamic load capacity:11500 lbhousing material:Cast Ironexpansion type:Non-Expansion Bearing (Fixed)locking device:Set ScrewB3-5/8 inseal type:Labyrinthrod hole diameter:3/4 infinish/coating:Powder Coated	d	1.0000 in
maximum rpm:3500 RPMslot width:0.5313 indynamic load capacity:11500 lbhousing material:Cast Ironexpansion type:Non-Expansion Bearing (Fixed)locking device:Set ScrewB3-5/8 inseal type:Labyrinthrod hole diameter:3/4 infinish/coating:Powder Coated	lubrication type:	Lubrication Fitting
slot width:0.5313 indynamic load capacity:11500 lbhousing material:Cast Ironexpansion type:Non-Expansion Bearing (Fixed)locking device:Set ScrewB3-5/8 inseal type:Labyrinthrod hole diameter:3/4 infinish/coating:Powder Coated	slot spacing:	3.0000 in
dynamic load capacity:11500 lbhousing material:Cast Ironexpansion type:Non-Expansion Bearing (Fixed)locking device:Set ScrewB3-5/8 inseal type:Labyrinthrod hole diameter:3/4 infinish/coating:Powder Coated	maximum rpm:	3500 RPM
housing material:Cast Ironexpansion type:Non-Expansion Bearing (Fixed)locking device:Set ScrewB3-5/8 inseal type:Labyrinthrod hole diameter:3/4 infinish/coating:Powder Coated	slot width:	0.5313 in
expansion type:Non-Expansion Bearing (Fixed)locking device:Set ScrewB3-5/8 inseal type:Labyrinthrod hole diameter:3/4 infinish/coating:Powder Coated	dynamic load capacity:	11500 lb
locking device:Set ScrewB3-5/8 inseal type:Labyrinthrod hole diameter:3/4 infinish/coating:Powder Coated	housing material:	Cast Iron
B3-5/8 inseal type:Labyrinthrod hole diameter:3/4 infinish/coating:Powder Coated	expansion type:	Non-Expansion Bearing (Fixed)
seal type:Labyrinthrod hole diameter:3/4 infinish/coating:Powder Coated	locking device:	Set Screw
rod hole diameter: 3/4 in finish/coating: Powder Coated	В	3-5/8 in
finish/coating: Powder Coated	seal type:	Labyrinth
	rod hole diameter:	3/4 in
series: B22400	finish/coating:	Powder Coated
	series:	B22400